



## TER series

Model	TER-1000	TER-1500	TER-2000	TER-3000	TER-5000	TER-8000	TER-10000	
Rated Capacity	1000VA	1500VA	2000VA	3000VA	5000VA	8000VA	10000VA	
Phase	Single							
Transformer	C.R.G.O. toroidal transformer							
Indicator	LED graphic							
Display Status	input / output , working and loading							
Input	Voltage	100~260 Vac						
	Frequency	50/60 Hz						
Output	Voltage	220/230/240 Vac optional						
	Precision	±8%						
Protection	Overload	Yes						
	High temperature	Yes						
	High/low voltage	Yes						
	Short circuit	Yes						
Delay Function	delay / un-delay (180/6 seconds selectable)							
Efficiency	98%							
Cooling system	Smart cooling for 3000Va and above							
Environmental	Operating temperature	0 - 40 °C						
	Relative humidity	10%~102% RH, non-condensing						
	Storage temperature	- 15 - 45 °C						
Appearance	AVR size (mm)	230x145x180			355x220x250			
	AVR N.W. (kg)	3.10	3.60	3.80	6.80	8.10	10.90	12.60
	Inner box size (mm)							
	Qty/Ctn							
	Carton size (mm)							
	Carton G.W. (kg)							